Transporter Li-ion

1500 kg










pull-out lithium ion battery weighs only 5kg



document holder
with standard 1 battery
configuration





simple, user friendly controls



creep (turtle) speed



Optional

2nd battery extends working time between charges



Our smallest powered truck - for light, medium or frequent use

Only 590mm wide & creed speed: use in narrow corridors & tight spaces, where other electric trucks can't go Weighs only 120kg: ideal for use in goods lifts, on ramps, tail lifts and in other weight restricted places Pull out lithium battery with approx working time of 5 hours, for light-medium use

Optional 2nd battery: swap discharged battery for the spare, for a longer working time of 11 hours

Fully powered lift & drive: no operator effort required

More information <u>here</u>

Transporter Li-ion:

Specification



Load Capacity	kg	1500
Service Weight	kg	120
Battery Weight	kg	5
Fork Height, lowered	mm	82
Fork Height, raised	mm	187
Fork Dimensions (H x W x L)	mm	55 x 150 x 1150
Distance Between Fork Arms	mm	560
Load Centre Distance	mm	600
Overall Length	mm	1550
Overall Width	mm	590
Height Towbar in Driving Position min/max	mm	750/1190
Aisle Width, 1000 x 1200 pallet crossways	mm	2160
Aisle Width, 800 x 1200 pallet crossways	mm	2025
Outer Turning Radius	mm	1360
Travel speed, laden/unladen	km/h	4/4.5
Lifting Speed, laden/unladen	m/s	0.017/0.020
Gradeability, laden/unladen	%	5/16
Battery Voltage/Rated Capacity (5h)	v/Ah	24/20
Drive Motor Rating (S2 60 min)	kW	0.75
Lift Motor Rating (S3 15%)	kW	0.5
Ground Clearance, centre of wheelbase	mm	25
Service Brake Type		Electromagnetic
Type of Drive Control		DC
Tyre Type driving wheels/loading wheels		PU/PU
Sound level at Driver's Ear	dB (A)	<74

Workplace Handling Solutions