INDICATOR 3200 Weight indicator with extended scale functions

BENEFITS

- Code entry, kg/lb toggle
- Relay for automatic dosing
- Display with backlight
- Internal clock for date/time
- For warehousing, dosing and mixing
- Bluetooth 4.0 for RAVAS WeightsApp



Top quality Advanced functions









INDICATOR 3200

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic tare by push button
- Tare entry by cursor function
- Totaling with sequence number
- Code entry for max. 5-digit codes, by cursor function
- Three data output modes: print, continuous and command/answer
- kg or lb toggle
- Internal clock (for recording date/time on printout)
- Error messages in display
- Power supply to printer switched on and off by indicator
- Automatic shut-off function, defined by parameter setting
- Low battery indication
- Bluetooth 4.0 for RAVAS WeightsApp

STANDARD SPECIFICATIONS

Display digital

Segments
 LCD, digit height 20 mm, backlight,

dual color

Graduation 0,1, 0,2, 0,5, 1, 2, 5, 10, 20 or 50 kg

(see specifications weighing system)

Housing plastic (ABS)

Bracket steel

Colour red (RAL 3000)Protection class IP65 / NEMA 4

Power supply
 12V (230V for stationary applications)

Power consumption 100 mA

Dimensions exc. bracket: 60 x 77 x 182 mm



OPTIONS*

- Printer output to thermal or matrix printer
- Bluetooth 2.0 or WLAN output
- Relay setpoint switch, for automatic dosing
- RS232 output for cable connection to truck terminal
- Multirange graduation (see specifications weighing system)
- Explosion proof version (Exd) (expected 2nd half of 2020)
- RDC, RAVAS Data Collector Software
- RIS, RAVAS Integration Software

RAVAS Europe B.V.

Veilingweg 17, 5301 KM Zaltbommel, The Netherlands T: +31 418 515220 E: salesoffice@ravas.com WWW.RAVAS.COM

