

Fully Powered Stackers

E-Twin

Stacker Capacity: 1000kg + 800kg



Compact manoeuvrability for medium duty pallet handling applications

- Lift and transport 2 pallets at the same time
- Lifts 800kg on forks to 1600mm. Lower initial lift forks have a lift capacity of 1000kg
- Can also be used as a low level electric pallet truck with 2000kg lift capacity
- Increased ground clearance of 210mm allows stacker to manoeuvre over ramps and small obstacles
- Fully powered AC technology: no operator effort required
- Handle head has an ergonomic design for maximum operator comfort
- Control buttons positioned to allow operation with either hand
- High quality programmable Curtis controller

E-Twin Specification:



Lift Type:	Fully Powered
Load Capacity:	1000kg + 800kg
Load Centre	600mm
Load Distance, centre of drive to fork axle	813mm
Wheelbase	1440mm
Service Weight (incl battery)	660 kg
Axle loading, laden operator/load side	750/1910kg
Axle loading, unladen operator/load side	450/210kg
Wheels	Polyurethane
Height, mast lowered	1860mm
Lift Height	1580mm
Height, mast extended	1895mm
Initial Lift	120mm
Fork height, lowered	90mm
Overall length	1776mm
Length to face of forks	666mm
Overall width	738/710mm
Fork dimensions	60/190/1150mm
Outside fork width, minimum/maximum	560mm
Ground Clearance	30mm
Aisle width, 1000 x 1200 UK pallet crossways	2274mm
Aisle width, 800 x 1200 Euro pallet lengthways	2198mm
Outer Turning radius	1442mm
Travel Speed, with load/without load	5/5.5 kmh
Lifting Speed, with load/without load	0.14/0.2 m/s
Lowering Speed, with load/without load	0.2/0.13 m/s
Maximum gradeability, with load/without load	8/16 %
Service Brake	Electromagnetic
Drive Motor rating S2 60 min	1.27 kW
Lift Motor Rating at S, 15%	2.2 kW
Battery voltage/rated capacity (5h)	24/224 V/Ah
Sound level at operators ear	74 db

Units 10 & 11 Bridgwater Court, Oldmixon Crescent, Weston-super-Mare BS24 9AY

Tel: 01934 621777 Email: sales@howardhandling.co.uk Web: www.howardhandling.co.uk